## Chapter 20.52 – Off-Street Parking and Loading Standards

#### Sections:

- 20.52.010 Purpose
- 20.52.020 Applicability
- 20.52.030 Requirements for Off-Street Parking
- 20.52.040 Off-Street Parking Spaces Required
- 20.52.050 Development Standards for Parking Areas
- 20.52.060 Parking for Nonresidential Uses in Residential Zoning Districts [New]
- 20.52.070 Parking Standards for Residential Uses
- 20.52.080 Off-Site Parking
- 20.52.090 Adjustments to Off-Street Parking Requirements
- 20.52.100 Parking Management Districts
- 20.52.110 Off-Street Loading Requirements

## 20.52.010 - Purpose

The purpose of this Chapter is to provide off-street parking and loading standards to:

- A. Provide for the general welfare and convenience of persons within the City by ensuring that sufficient parking facilities are available to meet the needs generated by specific uses and that adequate parking is provided, to the extent feasible;
- B Provide accessible, attractive, secure, and well-maintained off-street parking and loading facilities;
- C. Increase public safety by reducing congestion on public streets and to minimize impacts to public street parking available for coastal access and recreation;
- D. Ensure access and maneuverability for emergency vehicles; and
- E. Provide loading and delivery facilities in proportion to the needs of allowed uses.

## 20.52.020 – Applicability

- A. Off-street parking required. Each use, including a change or expansion of a use or structure, except as otherwise provided for in Chapter 20.50 (Nonconforming Uses and Structures) shall have appropriately maintained off-street parking and loading areas in compliance with the provisions of this Chapter. A use shall not be commenced and structures shall not be occupied until improvements required by this Chapter are satisfactorily completed.
- **B.** Change, enlargement, or intensification of use. Changes in use and enlargement or intensification of an existing shall require compliance with the off-street parking requirements of this Chapter, except as allowed in Chapter 20.50 (Nonconforming Uses and Structures).

## 20.52.030 - Requirements for Off-Street Parking

- **A. Parking required to be on-site.** Parking shall be located on the same lot or development site as the uses served, except for the following:
  - 1. **Townhouses and multi-tenant uses**. Where parking is provided on another lot within the same development site, the parking shall be located within 200 feet of the units they are intended to serve.
  - 2. Off-site parking agreement. Parking may be located off site with the approval of an off-site parking agreement in compliance with Subection 20.52.080.C (Parking agreement).
- **B. Permanent availability required.** Each parking and loading space shall be permanently available and maintained for parking purposes for the use it is intended to serve. The Director may authorize the temporary use of parking or loading spaces for other than parking or loading in conjunction with a seasonal or intermittent use allowed in compliance with Section 20.66.080 (Limited Term Permit).
- **C. Parking and loading to be unrestricted.** During business hours, parking and loading facilities required by this Division shall be available to the building's occupants, customers, and visitors without charge. A fee for parking may only be charged for spaces that exceed the requirements of this Chapter.
- **D. Maintenance.** Parking spaces, driveways, maneuvering aisles, turnaround areas, and landscaping areas shall be kept free of dust, graffiti, and litter. Striping, paving, walls, light standards, and all other facilities shall be permanently maintained in good condition.
- E. Vehicles for sale. Vehicles, trailers, or other personal property shall not be parked upon a private street, parking lot, or private property for the primary purpose of displaying the vehicle, trailer, or other personal property for sale, hire, or rental, unless the property is appropriately zoned, and the vendor is licensed to transact a vehicle sales business at that location.

## F. Calculation of spaces required.

- **1. Fractional spaces.** Fractional parking space requirements shall be rounded up to the next whole space.
- 2. Bench seating. Where bench seating or pews are provided, 18 linear inches of seating shall be considered to constitute a seat.
- **3. Gross floor area.** References to spaces per square foot are to be calculated on the basis of gross floor area unless otherwise specified.
- 4. Net public area. "Net Public Area" shall be defined as the total area accessible to the public within an eating and/or drinking establishment, excluding kitchens, restrooms, offices pertaining to the use, and storage areas.

- 5. Spaces per occupant. References to spaces per occupant are to be calculated on the basis of maximum occupancy approved by the City of Newport Beach Fire Department.
- 6. Spaces required for multiple uses. If more than one use is located on a site, the number of required off-street parking spaces shall be equal to the sum of the requirements prescribed for each use.
- **G. Nonconforming parking and loading.** Land uses and structures that are nonconforming due solely to the lack of off-street parking or loading facilities required by this Chapter, shall be subject to the provisions of Section 20.50.060 (Nonconforming Parking).

## 20.52.040 – Off-Street Parking Spaces Required

Off-street parking spaces shall be provided in compliance with Table 3.11, below. These standards shall be considered the minimum required to preserve the public health, safety, and welfare, and more extensive parking provisions may be required by the review authority in particular circumstances.

## TABLE 3-11 OFF-STREET PARKING REQUIREMENTS

Land Use	Parking Spaces Required	
Industry, Manufacturing & Processing, Warehous	ing Uses	
Food Processing	1 per 2,000 sq. ft.	
Handicraft Industry	1 per 500 sq. ft.	
Industry		
Small - 5,000 sq. ft. or less	1 per 500 sq. ft.	
Large - Over 5,000 sq. ft.	1 per 1,000 sq. ft.	
Industry, Marine Related	1 per 750 sq. ft.	
Personal Storage (Mini Storage)	2 for resident manager, plus additional for office as required by Minor Use Permit	
Research and Development	1 per 500 sq. ft.	
Warehousing and Storage 1 per 2,000 sq. ft., plus 1 per 350 sq. ft. Minimum of 10 spaces per use		
Wholesaling	1 per 1,000 sq. ft.	
Recreation, Education, and Public Assembly Uses		
Assembly/Meeting Facilities	1 per 3 seats or 1 per 35 sq. ft. used for assembly purposes	
Commercial Recreation and Entertainment	As required by Conditional Use Permit	
Cultural Institutions	1 per 300 sq. ft.	
Schools, Public and Private As required by Conditional Use Perm		
Residential Uses		
Accessory Dwelling Units	1 per unit; a minimum of 2 covered per site.	
Single-Unit Dwellings - Attached	2 per unit in a garage	
Single-Unit Dwellings - Detached	2 per unit in a garage	

TABLE 3-11 OFF-STREET PARKING REQUIREMENTS			
Land Use	Parking Spaces Required		
Single-Unit Dwellings - Balboa Island Multi-Unit Dwellings - up to 3 units	2 per unit in a garage 2 per unit in a garage, plus guest parking; 1 - 2 units, no guest parking required 3 units, 1 guest parking space		
Multi-Unit Dwellings - 4 units or more	2 per unit in a garage, plus 0.5 space per unit for guest parking		
Two-Unit Dwellings	2 per unit in a garage		
Live/work units [New]	2 per unit in a garage, plus 2 for guest/customer parking		
Senior Housing	1 per unit		
Retail Trade Uses			
Appliances, Building Materials, Home Electronics, Furniture, Nurseries, and Similar Large Warehouse- type Retail Sales and Bulk Merchandise Facilities Food and Beverage Sales Marine Rentals and Sales	1st 10,000 sq. ft 1space per 300 sq. ft. Over 10,000 sq. ft 1 space per 500 sq. ft. Plus 1 per 1,000 sq.ft. of outdoor merchandise areas 1 per 200 sq. ft.		
	1 per 1 000 er ft of let eree plue 1 per 250 er ft of		
Boat Rentals and Sales	1 per 1,000 sq. ft. of lot area, plus 1 per 350 sq. ft of office area		
Marine Retail Sales	1 per 250 sq. ft.		
Retail Sales	1 per 250 sq. ft.		
Shopping Centers Service Uses – Business, Financial, Medical, and Professional	l per 200 sq. ft.		
Convalescent Facilities	1 per 3 beds or as required by Conditional Use Permit		
Emergency Health Facilities	1 per 200 sq. ft.		
Financial Institutions and Related Services	1 per 250 sq. ft.		
Hospitals	1 per bed; plus 1 per resident doctor and 1 per employee.		
Offices* - Business, Corporate, General, Governmental			
Up to 50,000 sq. ft. 50,001 - 125, 000 sq. ft. 125,001 sq. ft. and greater	1 per 250 sq. ft. 1 per 300 sq. ft. 1 per 350 sq. ft.		
* Not more than 20% medical office uses.			
Offices - Medical and Dental Offices	1 per 200 sq. ft.		
Outpatient Surgery Facility Service Uses - General	1 per 250 sq. ft.		
Adult-Oriented Businesses	1 per 1.5 occupants or as required by Conditional Use Permit		
Ambulance Services	1 per 500 sq. ft.; plus 2 storage spaces.		
Animal Sales and Services			

Land Use	Parking Spaces Required		
Animal Boarding/Kennels	1 per 400 sq. ft.		
Animal Grooming	1 per 400 sq. ft.		
Animal Hospitals/Clinics	1 per 400 sq. ft.		
Animal Retail Sales	1 per 250 sq. ft.		
Artists' Studios	1 per 1,000 sq. ft.		
Catering Services	1 per 400 sq. ft.		
Care Uses			
Adult Day Care – Small (6 or fewer)	Spaces required for dwelling unit only.		
Adult Day Care - Large (7 or more)	2 per site for drop-off and pick-up purposes (in addition to the spaces required for the dwelling unit).		
Child Day Care – Small (6 or fewer)	Spaces required for dwelling unit only.		
Child Day Care - Large (9 to 14)	2 per site for drop-off and pick-up purposes (in addition to the spaces required for the dwelling unit).		
Day Care - General (15 or more)	1 per 7 occupants based on maximum occupancy allowed per license.		
Residential Care - General (7 to 14)	2 per site for drop-off and pick-up purposes (in addition to the spaces required for the dwelling unit).		
Eating and Drinking Establishments			
Accessory (open to public)	1 per each 3 seats or 1 per each 75 sq. ft. of net public area., whichever is greater		
Bars, Lounges, and Nightclubs	1 per each 4 persons based on allowed occupancy load or as required by Conditional Use Permit		
Food Service [New]	1 per 175 sq. ft. of gross area, including outdoor dining areas, but excluding the first 25% or 1,000 sq. ft of outdoor dining area, whichever is less.		
Food Service - Fast food	1 per 50 sq. ft., and 1 per 100 sq. ft. for outdoor dining areas		
Take-Out Service - Limited	1 per 250 sq. ft.		
Take-Out Service Only - no seating	1 per 50 sq. ft.		
Emergency Shelter	As required by Conditional Use Permit		
Funeral Homes and Mortuaries	1 per 35 sq. ft. of seating area		
Health/Fitness Facilities			
Small - 2,000 sq. ft or less	1 per 250 sq. ft.		
Large - Over 2,000 sq. ft.	1 per 200 sq. ft.		
Laboratories (medical, dental, and similar)	1 per 500 sq. ft		
Maintenance and Repair Services	1 per 500 sq. ft.		
Marine Services			
Boat Storage - Dry	0.33 per storage space or as required by Conditional Use Permit		
Boat Yards	As required by Conditional Use Permit		
Dry Docks	2 per dry dock		
Entertainment and Excursion Services	1 per each 3 passengers and crew members		

# TABLE 3-11OFF-STREET PARKING REQUIREMENTS

TABLE 3-11 OFF-STREET PARKING REQUIREMENTS			
Land Use	Parking Spaces Required		
Marine Service Stations	As required by Conditional Use Permit		
Sport Fishing Charters	1 per each 2 passengers and crew members		
Water Transportation Services - Office	1 per 100 sq. ft., minimum 2 spaces		
Personal Services			
Massage Establishments	1 per 200 sq. ft. or as required by Conditional Use Permit		
Nail Salons	1 per 80 sq. ft.		
Personal Services, General	1 per 250 sq. ft.		
Studio (dance, music, and similar)	1 per 250 sq. Ft.		
Postal Services	1 per 250 sq. ft.		
Printing and Duplicating Services	1 per 250 sq. ft.		
Recycling Facilities			
Collection Facility - Large	4 spaces minimum, but more may be required by the review authority		
Collection Facility - Small	As required by the review authority		
Visitor Accommodations			
Bed and Breakfast Inns	1 per guest room, plus 2 spaces		
Hotels	1 per 2 guest rooms		
Motels	1 per guest room or unit		
Recreational Vehicle Parks	As required by Conditional Use Permit		
Time Shares	1.2 per unit, plus 1 for each 50 sq. ft. of banquet seating or meeting area		
Transportation, Communications, and Infrastructu	Ire Uses		
Communication Facilities	1 per 500 sq. ft.		
Heliports and Helistops	As required by Conditional use Permit		
Marinas	0.75 per slip or 0.75 per 25 feet of mooring space		
Vehicle Rental, Sale, and Service Uses			
Vehicle/Equipment Rentals			
Office Only	1 per 250 sq. ft.		
Limited	1 per 300 sq. ft., plus 1 per rental vehicle (not including bicycles and similar vehicles)		
Vehicle/Equipment Rentals and Sales	1 per 1,000 sq. ft. of lot area		
Vehicle Sales, Office Only	1 per 250 sq. ft., plus 1 as required by DMV		
Vehicle/Equipment Repair (General and Limited)	1 per 300 sq. ft. or 5 per service bay whichever is more		
Vehicle/Equipment Services			
Automobile Washing	1 per 200 sq. ft.of office or lounge area; plus queue for 5 cars per washing station		
Service Station	1 per 300 sq. ft. or 5 per service bay whichever is more; minimum of 4		
Service Station with Convenience Market	1 per 200 sq. ft., in addition to 5 per service bay		
Vehicle Storage	1 per 500 sq. ft.		
Other Uses			
Caretaker Residence	1 per unit		

## TABLE 3-11OFF-STREET PARKING REQUIREMENTS

Land Use	Parking Spaces Required	
Special Events	As required by Municipal Code Chapter 11.03	
Temporary Uses	As required by the Limited Term Permit in compliance with Section 20.66.080	

## 20.52.050 – Development Standards for Parking Areas

- **A. Access to parking areas**. Access to off-street parking areas shall be provided in the following manner:
  - 1. Nonresidential and multi-unit. Parking areas for nonresidential and multi-unit uses:
    - a. Adequate and safe maneuvering aisles shall be provided within each parking area so that vehicles enter an abutting street or alley in a forward direction.
    - b. The Director may approve exceptions to the above requirement for parking spaces immediately adjoining a public alley, provided not more than 10 feet of the alley right-of-way is used to accommodate the required aisle width, and provided the spaces are set back from the alley the required minimum distances shown in the table, below.

Alley Width	Minimum Setback
15'-0" or less	5'-0"
15'-1" to 19'-11"	3'-9"
20'-0" or more	2'-6"

 TABLE 3-12

 PARKING SETBACK FROM ALLEY

- c. The first parking space within a parking area accessed from a public street shall be set back a minimum of 5 feet from the property line.
- 2. Access ramps. Ramps providing vehicle access to parking areas shall not exceed a slope of 15 percent. Changes in the slope of a ramp shall not exceed 11 percent and may occur at 5-foot intervals. Refer to Public Works Standard 160 A, B, and C. The Director of Public Works may modify these standards to accommodate specific site conditions.

## B. Location of parking facilities.

1. **Residential uses.** Parking facilities serving residential uses shall be located on the same site as the use the parking is intended to serve. Additional

requirements are provided in Section 20.52.070 (Parking Standards for Residential Uses), below.

- 2. Nonresidential uses. Parking facilities for nonresidential uses shall be located on the same site as the use the parking is intended to serve, except where an off site parking facility is approved in compliance with Section 20.52.080 (Off-site Parking).
- **3. Parking structures.** When adjacent to a residential zoning district, the development of structured parking, including rooftop parking shall require the approval of a Conditional Use Permit to mitigate potential impacts to adjacent residential uses.
- **4. Parking on slopes.** Parking shall not be allowed on slopes greater than 5 percent.

## C. Parking space and lot dimensions.

- 1. Minimum parking space and drive aisle dimensions. Each parking space, drive aisle, and other parking lot features shall comply with the minimum dimension requirements in Tables 3-x and 3-x, below, and as illustrated in Figure 3-x.
- 2. Width of one way aisle. The width of one way aisles may by reduced by the Public Works Director in unique situations arising from narrow lots or existing built conditions when traffic safety concerns have been addressed.

Minimum Standard Space Requirements		
Width	Length	
8 ft. 6 in.	17 ft	

 TABLE 3-13


 MINIMUM STANDARD PARKING SPACE SIZE

<b>TABLE 3-14</b>			
STANDARD VEHICLE SPACE REQUIREMENTS			


			<b>-</b> · · · ·	Aisle V		Width
Angle (degrees)	Stall Width (1)	Stall Depth (2)	Stall Length	One-Way	Two-Way	
Parallel	8 ft	8 ft	22 ft	14 ft	24 ft	
30	8 ft 6 in	16 ft	17 ft	14 ft	N/A	
45	8 ft 6 in	18 ft	17 ft	14 ft	N/A	
60	8 ft 6 in	19 ft	17 ft	18 ft	N/A	
90	8 ft 6 in	17 ft	17 ft	26 ft	26 ft	

(1) When the length of a parking space abuts a column, fence, wall, or other obstruction, the required width of the space shall be increased to 9 feet.


- (2) Measured perpendicular to aisle
- **3. Bumper overhang areas.** A maximum of 2.5 feet of the parking stall depth may be landscaped with low-growing, hearty materials in lieu of paving or the walkway may be increased, allowing a 2.5 foot bumper overhang while maintaining the required parking dimensions. Bumper overhang areas shall not encroach into required walkways, required landscape areas, or rights-of-way.
- 4. **Compact parking.** Compact parking spaces shall not be allowed.




30 Degree Angle Parking



45 Degree Angle Parking



60 Degree Angle Parking



90 Degree Parking

Figure 3-8 Parking Lot Dimensions

**D. Required parking area improvements.** Off-street parking areas shall have the following improvements:

## 1. Curbing and wheel stops.

- a. Continuous concrete curbing shall be installed a minimum of 5 feet from a wall, fence, building, or other structure. Curbs shall be a minimum of 6 inches high and 5<sup>1</sup>/<sub>2</sub> inches wide.
- b. The minimum standard curb radius shall be 6 feet at all aisle corners. Alternative curb radii may be approved by the Director of Public Works.
- c. Individual wheel stops may be provided in lieu of continuous curbing when the parking is adjacent to a landscaped area, and the parking area drainage is directed to the landscaped area subject to the approval of the Director of Public Works. Wheel stops shall be placed to allow for 2 feet of vehicle overhang area within the dimension of the parking space.
- 2. **Drainage.** Parking lots shall be designed in compliance with the storm water quality and quantity standards of the City's Best Management Practices and the City's Standard Specifications and Plans.
- **3.** Landscaping. [New] Landscaping for surface parking lots with 10 or more spaces shall be provided as follows.

## a. Perimeter parking lot landscaping. [New]

- (1) Adjacent to streets.
  - (a) Parking areas abutting a public street shall be designed to provide a perimeter landscape strip a minimum 5 feet wide between the street right-of-way and parking area. The Director may grant an exception to this requirement if existing structures, substandard lots, or unique site conditions preclude its implementation. In this case, the maximum feasible planting strip area shall be provided based on site conditions.
  - (b) Landscaping, other than trees, shall be designed and maintained to screen cars from view from the street and shall be maintained at approximately 36 inches in height.
  - (c) Screening materials may include a combination of plant materials, earth berms, raised planters, low walls, or other screening devices that meet the intent of this requirement as approved by the Director.
  - (d) Plant materials, walls, or structures within a traffic sight area of a driveway shall not exceed 36 inches in height in compliance with Section 20.30.110 (Traffic Safety Visibility Area).

- (a) Parking areas for nonresidential uses adjoining residential uses shall provide a landscaped buffer yard with a minimum of 5 feet in width between the parking area and the common property line bordering the residential use. A solid masonry wall and landscaping in compliance with Subsection 20.30.020.D (Screening and buffering between different zoning districts) shall be provided along the property line.
- (b) Trees shall be provided at a rate of one for each 30 feet of landscaped area and shall be a minimum 24 inch box container at time of planting.

## b. Interior parking lot landscaping. [New]

- (1) Trees required.
  - (a) Number and location. Trees shall be evenly spaced throughout the interior parking area at a rate of one tree for every 5 parking spaces. Trees shall be located in planters that are bounded on at least 3 sides by parking area paving. Planters shall have a minimum interior dimension of 6 feet.
  - (b) Size. All trees within the parking area shall be a minimum 24 inch box container at time of planting.
- (2) Ends of aisles. All ends of parking aisles shall have landscaped islands planted with trees, shrubs, and ground cover.
- (3) Larger projects. Parking lots with more than 100 spaces shall provide an appropriate entry feature consisting of a concentration of landscape elements, including specimen trees, flowering plants, enhanced paving, and project identification.
- **4. Lighting.** Parking lots shall be lighted so that there is an average illumination over the entire lot of 2.5 footcandles and a minimum of 1.0 footcandle.

## 5. Stall markings, directional arrows, and signs.

- a. Parking spaces shall be clearly outlined with 4-inch-wide lines painted on the surface of the parking facility. Car pool and van pool spaces shall be clearly identified for exclusive use of car pools and van pools.
- b. Parking spaces for the disabled shall be striped and marked so as to be clearly identified in compliance with the applicable Federal, State, and City standards.
- c. Driveways, circulation aisles, and maneuvering areas shall be clearly marked with directional arrows and lines to ensure the safe and efficient flow of vehicles.

- d. The Director of Public Works may require the installation of traffic signs in addition to directional arrows to ensure the safe and efficient flow of vehicles in a parking facility.
- 6. Surfacing. Parking spaces and maneuvering areas shall be paved and permanently maintained with asphalt, concrete, or interlocking paving stones or other City approved surfaces.
- E. Enclosed parking. The following regulations shall apply to enclosed commercial offstreet parking:
  - 1. Doors shall remain open during regular business hours;
  - 2. A sign shall be posted on the business frontage that advises patrons of the availability and location of parking spaces;
  - 3. Signs shall be posted on the site containing the following information:
    - a. Doors are to remain open during business hours; and
    - b. A number to call for Code Enforcement.
  - 4. The location, size, and color of the signs required above shall be approved by the Department.

## 20.52.060 – Parking for Nonresidential Uses in Residential Zoning Districts [New]

Where parking lots for nonresidential uses are allowed in residential zoning districts in compliance with Chapter 20.18 (Residential Zoning Districts), they shall be developed in compliance with the following requirements in addition to other applicable standards provided in this Chapter.

- **A. Conditional Use Permit required.** Approval of a Conditional Use Permit shall be required in order to locate a parking lot intended for nonresidential use within a residential zoning district.
- **B.** Location of parking area. The parking area shall be accessory to, and for use of, one or more abutting nonresidential uses allowed in an abutting commercial zoning district. The Commission may grant a waiver for noncontiguous parking lots, but only under all of the following conditions:
  - 1. The parking lot is designed to be compatible with the neighborhood;
  - 2. There are no residential uses between the parking lot and the commercial zoning district;
  - 3. The location of the parking lot does not fragment the adjacent neighborhood;
  - 4. The parking lot is not detrimental or injurious to property and improvements in the neighborhood; and
  - 5. The parking lot is located within a reasonable walking distance of the use to which it is an accessory.

- **C. Access.** Access to parking lots shall be from commercial streets or alleys. An exception may be granted by the Commission if no commercial streets are available for access.
- **D. Passenger vehicle parking only.** Parking lots shall be used solely for the parking of passenger vehicles.
- E. Signs. No signs, other than signs designating entrances, exits, and conditions of use shall be maintained in parking areas. Signs shall not exceed 4 square feet in area and 5 feet in height. The number and location shall be approved by the Director before installation.
- **F. Perimeter wall.** The parking lot shall have a solid masonry wall 6 feet in height along all interior property lines adjacent to residential zoning districts and 36 inches in height adjacent to streets and the front setback area of an abutting residential use.
- **G. Development standards.** The parking lot shall be developed in compliance with the development standards of this Chapter and the outdoor lighting standards in Section 20.30.060 (Outdoor lighting).
- **H. No overnight parking.** Overnight parking shall be prohibited and the parking lot shall be secured after business hours to prevent any use of the facility.

## 20.52.070 – Parking Standards for Residential Uses

- A. Parking space and driveway dimensions.
  - 1. Minimum interior dimensions.
    - a. Lots less than 40 feet wide. Required parking spaces shall have a minimum interior width of 17 feet, 6 inches and a minimum interior depth of 19 feet.
    - **b.** Lots 40 feet wide and greater. Required parking spaces shall have a minimum interior width of 18 feet, 6 inches and a minimum interior depth of 20 feet.
  - 2. **Tandem parking.** Where tandem parking is provided, one space may have a minimum interior depth of 16 feet, provided the space is not used to meet the requirements for covered parking. Tandem parking up to a maximum of 2 cars in depth shall be allowed.
  - **3. Driveway width.** Driveways visible from a public right-of-way shall not be wider than required to access an adjacent garage as follows:
    - a. One car garage: 10 feet wide
    - b. Two car garage: 20 feet wide
    - c. Three car garage: 25 feet wide
    - d. Four car garage: 32 feet wide

4. Vertical clearances. The minimum unobstructed vertical clearance for parking spaces shall be 7 feet, except that the front 4 feet may have a minimum vertical clearance of 4 feet.

## B. Access to parking.

- 1. **Direct access required.** Each parking space shall be capable of being accessed directly from an adjoining vehicular right-of-way or over an improved hard surfaced driveway, except for approved tandem parking spaces.
- 2. Clear access required. Where access to a required parking space is taken over a driveway, the driveway shall be maintained free and clear at all times except for the parking of currently registered, licensed motor vehicles, and for temporary obstructions that are incidental to the use of the property. Temporary obstructions in the driveway shall be allowed only for a period up to 72 hours.

#### C. Location of parking.

- 1. Allowed parking areas. Parking is allowed only in required permanent parking areas and on driveways leading to required parking areas. Under no circumstances shall landscaped and hardscaped areas, other than driveways, be used for the temporary parking of vehicles.
- 2. Garages facing the street. Garages with doors that face the street that are located within 20 feet of the front property line shall be equipped with automatic roll-up doors.
- **3. Parking located in required setback areas.** The following requirements shall apply to the parking or storage of motor vehicles, recreational vehicles, watercraft, trailers, and similar items in residential zoning districts:
  - a. Front setback areas. Parking or storage in required front setback areas shall be prohibited, except on driveways in front of garages that set back a minimum of 20 feet from the front property line.
  - **b. Side setback areas.** Parking or storage in required side setback areas (behind the rear line of the required front setback area) shall be allowed.
  - c. Rear setback areas without alleys. Parking or storage in required rear setback areas shall be allowed.
  - d. Rear setback areas with alleys. Parking or storage in required rear setback areas shall not be allowed.

## 20.52.080 – Off-Site Parking

**A. Conditional Use Permit required.** Approval of a Conditional Use Permit shall be required for a parking facility or any portion of required parking that is not located on the same site it is intended to serve.

- **B. Findings.** In order to approve a Conditional Use Permit for an off site parking facility the Commission shall make all of the following findings in addition to those required for the approval of a Conditional Use Permit:
  - 1. The parking facility is located within a convenient distance to the use it is intended to serve;

20.52

- 2. Use of the parking facility will not create undue traffic hazards or impacts in the surrounding area; and
- 3. The parking facility will be permanently available, marked, and maintained for the use it is intended to serve.
- **C. Parking agreement.** A parking agreement, which guarantees the long term availability of the parking facility for the use it is intended to serve, shall be recorded with the County Recorder's Office. The agreement shall be in a form approved by the City Attorney and the Director

## D. Loss of off site Parking.

- 1. Notification of City. The owner or operator of a business that uses approved off site parking facility to satisfy the parking requirements of this Chapter shall immediately notify the Director of any change of ownership or use of the property where the spaces are located, or changes in the use that the spaces are intended to serve, or of any termination or default of the agreement between the parties.
- 2. Effect of termination of agreement. Upon notification that the agreement for the required off site parking has terminated, the Director shall establish a reasonable time in which one of the following shall occur:
  - a. Substitute parking is provided that is acceptable to the Director; or
  - b. The size or capacity of the use is reduced in proportion to the parking spaces lost.

## 20.52.090 – Adjustments to Off-Street Parking Requirements

The number of parking spaces required by this Chapter may be reduced only in compliance with the following standards and procedures.

- **A. ADA compliance.** The Director may administratively reduce parking requirements due to a loss of parking spaces because of increased ADA requirements associated with tenant improvements.
- **B. Reduction of required off-street parking.** Off-street parking requirements may be reduced with the approval of a Conditional Use Permit in compliance with Section 20.66.090 (Conditional Use Permits and Minor Use Permits) as follows:
  - **1. Reduced parking demand.** Required off-street parking may be reduced with the approval of a Conditional Use Permit in compliance with the following conditions:

- a. The applicant has provided sufficient data, including a parking study if required by the Director, to indicate that parking demand will be less than requirement (e.g., City parking lot located nearby, greater than normal walk in trade, mixed use development); and
- b. A parking management plan shall be prepared in compliance with Subsection C (Parking management plan), below
- 2. Joint use of parking facilities. Required off-street parking may be reduced with the approval of a Conditional Use Permit where two or more nonresidential uses on the same site or immediately adjacent sites have distinct and differing peak parking demands (e.g. a theater and a bank). The review authority may grant a joint use of parking spaces between the uses that results in a reduction in the total number of required parking spaces in compliance with the following conditions:
  - a. The most remote space is located within a convenient distance to the use it is intended to serve;
  - b. The amount of reduction is no greater than the number of spaces required for the least intensive of the uses sharing the parking;
  - c. The probable long-term occupancy of the structures, based on their design, will not generate additional parking demand;
  - d. The applicant has provided sufficient data, including a parking study if required by the Director, to indicate that there is no conflict in the peak parking demand for the uses proposing to make joint use of the parking facilities;
  - e. The property owners involved in the joint use of parking facilities shall record a parking agreement approved by the Director and City Attorney. The agreement shall be recorded with the County Recorder, and a copy shall be filed with the Department; and
  - f. A parking management plan shall be prepared in compliance with Subsection C (Parking management plan), below
- **C. Parking management plan.** When a parking management plan to mitigate impacts associated with a reduction in the number of required parking spaces is required by this Chapter, the parking management plan shall include the following:
  - 1. Restricting land uses to those that have hours or days of operation so that the same parking spaces can be used by two or more uses without conflict;
  - 2. Restricting land uses with high parking demand characteristics;
  - Securing off site parking in compliance with Section 20.52.080 (Off-site Parking); and
  - 4. Providing parking attendants and valet parking.

**D. Required Data.** In reaching a decision to allow a reduction of required parking spaces, the review authority shall consider data submitted by the applicant or collected/prepared at the applicant's expense.

## 20.52.100 – Parking Management Districts

Properties within a parking management district, established through the PM (Parking Management) Overlay District, may be exempted from all or part of the off-street parking requirements of this Chapter in compliance with the provisions of the adopted parking management district plan.

## 20.52.110 – Off-Street Loading Requirements

#### A. Number of loading spaces required.

- 1. Up to 10,000 square feet. Nonresidential uses with less than 10,000 square feet of gross floor area shall provide one off-street loading space, which may be combined with up to 2 off-street parking spaces.
- 2. **10,000 square feet or greater.** Nonresidential uses with 10,000 square feet of gross floor area or more shall provide off-street loading space(s) in compliance with Table 3-15, below.
- **3. Uses not listed.** Requirements for uses not specifically listed shall be determined by the Director based upon the requirements for comparable uses and upon the particular characteristics of the proposed use.

Type of Land Use	Total Gross Floor Area	Loading Spaces Required	
Manufacturing, research	10,000 – 30,000 sq. ft.	One	
and development, institutional, and service uses	30,001 sq. ft. or more	One for each additional 20,000 sq. ft., plus additional as required by Director.	
Office uses	30,000 to 60,000 sq. ft.	One	
	60,001 + sq. ft.	One for each additional 30,000 sq. ft., plus additional as required by Director.	
Commercial and other	10,000 to 20,000 sq. ft.	One	
allowed uses	20,001 + sq. ft.	One for each additional 10,000 sq. ft., plus additional as required by Director.	

#### TABLE 3-15 REQUIRED LOADING SPACES

## B. Development standards for off-street loading areas.

- **1. Dimensions.** Loading spaces shall be at least 10 feet in width, 25 feet in length, with 14 feet of vertical clearance.
- 2. Lighting. Loading areas shall have lighting capable of providing adequate illumination for security and safety. Lighting sources shall be shielded to prevent light spill beyond the property line. Lighting fixtures shall be energy-efficient and in scale with the height and use of adjacent structure(s).
- **3.** Location. Loading spaces shall be located and designed as follows:
  - a. As near as possible to the main structure and limited to the rear two-thirds of the lot, if feasible;
  - b. Situated to ensure that the loading facility is screened from adjacent streets to the greatest degree feasible;
  - c. Situated to ensure that loading and unloading takes place on-premises and in no case within an adjacent public right-of-way or other traffic circulation areas on-premises;
  - d. Situated to ensure that vehicular maneuvers occur on-premises; and
  - e. Situated to avoid adverse impacts upon neighboring residential properties.
- **4. Striping.** When required by the review authority, loading areas shall be striped and identified for "loading only." The striping shall be maintained in good condition at all times.