



CONSTRUCTION NOTES:

- ① 8"X4" VCP (OR SDR-35 PVC) WYE (F X M X F).
- ② 4" VCP (OR SDR-35 PVC) 22.5° BEND (F X M).
- ③ INCOMING 4" LATERAL PER APPLICABLE PORTIONS OF STD 406.
- ④ FRAME & COVER SHALL BE BROOKS PRODUCT NO. 4TT MARKED "SEWER" PER APPLICABLE PORTIONS OF STD 513.
- ⑤ 8" VCP (OR SDR-35 PVC) 45° BEND (F X M).
- ⑥ 8"X8" VCP (OR SDR-35 PVC) WYE (F X F X F).
- ⑦ 8" VCP (OR SDR-35 PVC) PIPE.
- ⑧ 8" RUBBER MECHANICAL BANDED SEAL CLAMP. FERNCO OR CITY-APPROVED EQUAL.

GENERAL NOTES:

- 1. UP TO TWO RESIDENTIAL WYES PER CHIMNEY WITH CLEANOUTS AT PROPERTY LINE WILL BE PERMITTED DEPENDING ON SEWER MAIN DEPTH.
- 2. CHIMNEY INSTALLATION IS ONLY PERMITTED UNDER THE SPECIAL APPROVAL OF CITY.
- 3. COMMERCIAL LATERALS MAY NOT BE STACKED ON A CHIMNEY WITH OTHER LATERALS.
- 4. SEWER PIPE AND FITTINGS SHALL BE BEDDED WITH 3/4" CRUSHED ROCK MATERIAL PER STD 323. IN AREAS OF GROUND WATER OR TIDE WATER, 3/8" CRUSHED ROCK SHALL BE USED.
- 5. VCP SHALL BE HIGH STRENGTH.

NOTE:

IF EXISTING PIPE IS VCP, USE VCP. IF EXISTING PIPE IS SDR, USE SDR.

FORMER CITY STANDARD PLAN NUMBER (2004 EDITION): STD 408-L

APP. <i>James M. Hinkle</i>	51568	11/24/2020			
CITY ENGINEER	RCE	DATE			
			NO.	DATE	DESCRIPTION OF REVISIONS

CITY OF NEWPORT BEACH DEPARTMENT OF PUBLIC WORKS

DRAWN: P. KHARAZMI	SEWER LATERAL CHIMNEY CONNECTION(S)	STANDARD DRAWING NO.
DATE: 11/3/2020		409
		SHEET 1 OF 1