



### SURVEY MONUMENT PLACEMENT

N.T.S.

**NOTE:**

2" GALVANIZED IRON PIPE MONUMENTS SHALL BE SET AT EACH BOUNDARY CORNER OF A SUBDIVISION, ALONG EXTERIOR BOUNDARIES AT INTERVALS NOT OVER 500 FEET, AT THE BEGINNING AND END OF EXTERIOR PROPERTY LINE CURVES. 1" GALVANIZED IRON PIPE MONUMENTS SHALL BE SET AT INTERIOR LOT/PARCEL CORNERS AND PROPERTY LINE CURVES.

DESCRIPTION	MINIMUM SIZE	MINIMUM LENGTH	RELATIONSHIP TO SURFACE
GALVANIZED IRON PIPE WITH 5/8" LONG BRASS NAIL AND 3/4" DIAMETER BRASS TAG	2" - EXTERNAL BDY 1" - INTERNAL BDY	36" 24"	PIPE SHALL BE FLUSH NAIL AND TAG AND BE RECESSED 1/4" MIN BELOW TOP OF IRON PIPE
GALVANIZED SPIKE WITH 3/4" GALVANIZED WASHER AND 1 1/2" BRASS TAG	3/8" SPIKE	0'-4"	TOP OF SPIKE TO BE FLUSH OR RECESSED SLIGHTLY BELOW TOP OF FINISHED SURFACE
LEAD WITH 5/8" LONG BRASS NAIL AND 3/4" DIAMETER BRASS TAG			NAIL AND TAG SHALL BE RECESSED 1/4" BELOW TOP OF EXISTING SURFACE
3/4" DIAMETER BRASS TAG IN EPOXY			TAG SHALL BE RECESSED 1/4" BELOW TOP OF EXISTING SURFACE

FORMER CITY STANDARD PLAN NUMBER (2004 EDITION): STD 117-L

APP.	51568 RCE	11/24/2020 DATE	
CITY ENGINEER			
			NO.    DATE    DESCRIPTION OF REVISIONS

## CITY OF NEWPORT BEACH DEPARTMENT OF PUBLIC WORKS

DRAWN: P. KHARAZMI	<h1 style="margin: 0;">SUBDIVISION AND LOT CORNER MONUMENTS</h1>	STANDARD DRAWING NO. <h1 style="margin: 0;">117</h1> SHEET 1 OF 1
DATE: 11/3/2020		