


TYPICAL PLATFORM SECTION

NOTES:

- TIMBER SHALL BE SELECT STRUCTURAL DOUGLAS FIR TREATED WITH PRESERVATIVE APPROVED BY THE STATE OF CALIFORNIA (CALIFORNIA COASTAL COMMISSION AND REGIONAL WATER QUALITY CONTROL BOARD).
- 2. FIELD CUTS AND BORED HOLES SHALL RECEIVE A BRUSH COAT OF PRÉSERVATIVE TREATMENT PER STATE AND FEDERAL GUIDELINES.
- 3. FASTENERS SHALL BE STAINLESS, HOT DIP GALVANIZED OR EPOXY-COATED STEEL.
- 4. WALKING SURFACES SHALL HAVE A SKID RESISTANT FINISH, SUCH AS UNPAINTED TIMBER OR GRIT ON TIMBER, OR OTHER SURFACING DEEMED APPROPRIATE FOR THE INTENDED SERVICE, BY THE CITY OF.
- 5. NON-STRUCTURAL MEMBERS MAY BE ALTERNATIVE MATERIALS SUCH AS COMPOSITE DIMENSIONAL LUMBER, SUBMIT PRODUCT SPECIFICATIONS TO THE CITY.
- 6. JOIST SPLICES ARE NOT PERMITTED BETWEEN PILES.
- 7. DESIGN TO BE BY A CALIFORNIA LICENSED CIVIL OR STRUCTURAL ENGINEER.



SINGLE OR JOINT
TE: 11/3/2020 RESIDENTIAL USE PLATFORM SECTION

609 SHEET 1 OF 1