



TYPICAL SIGN INSTALLATION

NOTES:

1. SIGN SHALL BE STANDARD SIZE PER THE CALIFORNIA MUTCD UNLESS OTHERWISE SHOWN. SIGN SHALL BE MADE OF ALUMINUM (0.08 INCH THICKNESS).
2. REFLECTIVE SHEETING SHALL BE 3M HIGH INTENSITY PRISMATIC (TYPE 4) OR GREATER, OR APPROVED EQUAL.
3. NEW SIGN POSTS SHALL BE 14 GAUGE, 2 INCH SQUARE (O.D.) UNISTRUT INSTALLED INTO A 12 GAUGE 2-1/4 INCH UNISTRUT (O.D.) BASE. UNISTRUT BASE SHALL BE INSTALLED AT A DEPTH OF 18 INCHES IN CONCRETE AND 30 INCHES IN DIRT. CONTRACTOR SHALL USE LOCATION PRIOR TO INSTALLING SIGN.
4. SIGN MOUNTING HARDWARE AND BRACKETS SHALL BE 5/16 INCH STAINLESS STEEL. ANTI-SEIZE LUBRICANT SHALL BE APPLIED TO MOUNTING HARDWARE PRIOR TO INSTALLATION.
5. SIGNS SHALL BE INSTALLED AT A CLEAR HEIGHT OF 7 FEET UNLESS OTHERWISE SHOWN ON PLANS. LOCATION OF SIGNS SHOWN ON PLANS IS APPROXIMATE AND SHALL BE APPROVED BY THE CITY PRIOR TO INSTALLATION.

APP.	51568 CITY ENGINEER RCE	11/24/2020 DATE													
			<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">NO.</th> <th style="width: 10%;">DATE</th> <th style="width: 80%;">DESCRIPTION OF REVISIONS</th> </tr> </thead> <tbody> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </tbody> </table>	NO.	DATE	DESCRIPTION OF REVISIONS									
NO.	DATE	DESCRIPTION OF REVISIONS													

CITY OF NEWPORT BEACH DEPARTMENT OF PUBLIC WORKS

DRAWN: P. KHARAZMI	<h1 style="margin: 0;">TYPICAL TRAFFIC SIGN INSTALLATION</h1>	STANDARD DRAWING NO. <h2 style="margin: 0;">924</h2>
DATE: 11/3/2020		SHEET 1 OF 1