CITY OF NEWPORT BEACH

COMMUNITY DEVELOPMENT DEPARTMENT BUILDING DIVISION

100 Civic Center Drive | P.O. Box 1768 | Newport Beach, CA 92658-8915 www.newportbeachca.gov | (949) 644-3200

TENANT IMPROVEMENT GENERAL NOTES

- 1. All work shall comply with 2013 CBC; 2013 CPC; 2013 CEC; 2013 CMC; 2013 California Energy Code & the Newport Beach Municipal Code (NBMC).
- 2. Provide non-combustible interior partitions using metal studs in Type I and Type II construction. CBC 603.1 and Table 601
- 3. All corridors shall maintain a minimum 44 inch clear width throughout the tenant space and building exits, when serving 50 or more persons. CBC 1018.2
- 4. Corridors and exit paths shall have egress lighting with emergency power back-up power supply. CBC 1006.3
- 5. Exit signage shall have an alternate power source. CBC 1011.1 & 1011.6.3
- 6. The maximum occupant load shall be posted in each assembly, dining and/or waiting area, as stated on the plans. CBC 1004.3
- 7. Provide fire extinguishers (2-A.10-B, C) throughout each tenant suite, minimum one extinguisher per suite, with maximum distance of 75 ft from any point to a fire extinguisher.
- 8. Fire sprinkler drawings shall be submitted and permit issued within two weeks from building permit issuance.
- 9. Fire alarm drawings shall be submitted and permit issued within two weeks from building permit issuance.

ELECTRICAL, MECHANICAL & PLUMBING

- 1. Use rigid metal conduit in all areas exposed to weather.
- 2. Provide ground wire inside all flexible metal conduit.
- 3. Metal conduit shall not be installed in contact with earth.
- 4. All equipment to be U.L. listed or equivalent.
- 5. All waste lines shall be installed with a minimum 2% slope.
- 6. Bathroom floors and walls to have hard, smooth, nonabsorbent finish to a height of 48 inches above floor.